

## Theme

You can use the Theme function to change the colors of lower levels. The top theme change tag is `<data-role="page">`. The colors of Header, Footer, Panel and UX Component are changed.

### Base code

Add **`data-theme="[a~g]"`** to the top div tag to which the theme is applied.

### Header Title

Applying the Page theme will change the colors of Header, Panel and Footer.

### Footer Title

```
<div data-role="header" data-theme="e">
  <h1>Header Title</h1>
</div>
<div data-role="content">
  <p>Page Applying the Page theme will change
  the colors of Header, Panel and Footer.</p>
</div>
<div data-role="footer" data-theme="e">
  <h1>Footer Title</h1>
</div>
```

## Theme Sample

If a theme is applied, all the colors of lower components are changed. If you don't want to apply a upper level theme, define a different theme to the top div tag of the element you don't want to use.

Select theme:

data-theme="a"  

---

### a Apply theme (data-theme="a")

---

#### Header

[New](#)

#### Bar theme "a"

[Save](#)

```
<div data-role="header" data-position="inline" data-theme="a">
  <a href="#" data-icon="plus">New</a>
  <h1>Bar theme "a"</h1>
  <a href="#" data-icon="arrow-r" data-iconpos="right">Save</a>
```

```
<div>
```

### Footer

[left](#) [right](#) [up](#) [down](#)

```
<div data-role="footer" data-theme="a">
```

```
  <a href="#" data-role="button" data-icon="arrow-l" data-iconpos="right">left</a>
```

```
  <a href="#" data-role="button" data-icon="arrow-r" data-iconpos="right">right</a>
```

```
  <a href="#" data-role="button" data-icon="arrow-u" data-iconpos="right">up</a>
```

```
  <a href="#" data-role="button" data-icon="arrow-d" data-iconpos="right">down</a>
```

```
</div>
```

### Button

[Button](#)

```
<a href="#" data-role="button" data-theme="a">Button</a>
```

### Panel

#### Panel a

```
<div class="ui-bar-a">
```

```
  <h4>Panel a</h4>
```

```
</div>
```

### Tabs

[One](#)

[Two](#)

[Three](#)

```
<div data-role="navbar" data-theme="a">
```

```
  <ul>
```

```
    <li><a href="#" class="ui-btn-active">One</a></li>
```

```
    <li><a href="#">Two</a></li>
```

```
    <li><a href="#">Three</a></li>
```

```
  </ul>
```

```
</div>
```

### Form

Text :

Slider:

```
<form>
```

```
  <div data-role="content" data-theme="a">
```

```
    <div data-role="fieldcontain">
```

```
      <label for="name">Text :</label>
```

```
      <input type="text" id="name"/>
```

```
    </div>
```

```
    <div data-role="fieldcontain">
```

```
      <label for="slider">Slider:</label>
```

```
      <input type="range" id="slider" value="0" min="0" max="100" />
```

```
    </div>
```

```
  </div>
```

```
</form>
```

## Menu

Menu

[E-government mobile standard framework overview](#)

```
<ul data-role="listview" data-inset="true" data-theme="a" data-dividertHEME="a">
  <li data-role="list-divider">Menu</li>
  <li><a href="#menu1" data-rel="dialog" data-transition="slide">E-government mobile standard
  framework overview</a></li>
</ul>
```

## Dialog

[ActionSheet Dialog data-theme="a" Overlay Dialog data-theme="a" Alert Dialog data-theme="a" Confirm Dialog data-theme="a" Show prompt Dialog data-theme="a"](#)

## Grid

**ui-block-a**

**ui-block-b**

```
<div class="ui-grid-a">
  <div class="ui-block-a"><div class="ui-body-a" align="center"><h3>ui-block-
  a</h3></div></div>
  <div class="ui-block-b"><div class="ui-body-a" align="center"><h3>ui-block-
  b</h3></div></div>
</div>
```

## List

Nested List

Numbered List

Split Button

List Divider

Count Bubble

Thumbnail

List Icon

Content Formatting

Search Filter Bar

```
<ul data-role="listview" data-inset="true" data-theme="a">
  <li>Nested List</li>
  <li>Numbered List</li>
  <li>Split Button</li>
  <li>List Divider</li>
  <li>Count Bubble</li>
  <li>Thumbnail</li>
  <li>List Icon</li>
  <li>Content Formatting</li>
  <li>Search Filter Bar</li>
</ul>
```

## Date / Time Picker

Android shape

[date picker](#)

Calendar shape



[date picker](#)

```

<div data-role="fieldcontain">
  <label for="andate">Android shape</label>
  <input name="mydate" id="andate" type="date" data-role="datebox" data-options='{ "page": "a",
    "button": "a"}'>
</div>
<div data-role="fieldcontain">
  <label for="caldate">Calendar shape</label>
  <input name="mydate" id="caldate" type="date" data-role="datebox" data-options='{ "mode":
    "calbox", "button": "a"}'>
</div>

```

### Check Box

Check Box :

- check 1
- check 2
- check 3

```

<div data-role="fieldcontain">
  <fieldset data-role="controlgroup" data-type="horizontal">
    <legend data-theme="a">Check Box :</legend>
    <input type="checkbox" name="checkbox-6" id="checkbox-6" class="custom" />
    <label for="checkbox-6" data-theme="a">check 1</label>
    <input type="checkbox" name="checkbox-7" id="checkbox-7" class="custom" />
    <label for="checkbox-7" data-theme="a">check 2</label>
    <input type="checkbox" name="checkbox-8" id="checkbox-8" class="custom" />
    <label for="checkbox-8" data-theme="a">check 3</label>
  </fieldset>
</div>

```

### Radio

Radio Button:

- radio 1
- radio 2

```

<fieldset data-role="controlgroup">
  <legend data-theme="a">Radio Button:</legend>
  <input type="radio" name="radio-choice-1" id="radio-choice-1" value="choice-1"
    checked="checked" />
  <label for="radio-choice-1" data-theme="a">radio 1</label>
  <input type="radio" name="radio-choice-1" id="radio-choice-2" value="choice-2" />
  <label for="radio-choice-2" data-theme="a">radio 2</label>
</fieldset>

```

### Icon

[arrow-l](#) [arrow-r](#) [arrow-u](#) [arrow-d](#) [delete](#) [plus](#) [minus](#) [check](#) [gear](#) [refresh](#) [forward](#) [back](#) [grid](#) [star](#) [alert](#) [info](#) [search](#) [home](#) [phone](#) [mail](#)

```

<div data-role="controlgroup" data-type="horizontal">

```

```
<a href="#" data-role="button" data-icon="arrow-l" data-iconpos="notext" data-theme="a">arrow-l</a>
<a href="#" data-role="button" data-icon="arrow-r" data-iconpos="notext" data-theme="a">arrow-r</a>
<a href="#" data-role="button" data-icon="arrow-u" data-iconpos="notext" data-theme="a">arrow-u</a>
<a href="#" data-role="button" data-icon="arrow-d" data-iconpos="notext" data-theme="a">arrow-d</a>
<a href="#" data-role="button" data-icon="delete" data-iconpos="notext" data-theme="a">delete</a>
<a href="#" data-role="button" data-icon="plus" data-iconpos="notext" data-theme="a">plus</a>
<a href="#" data-role="button" data-icon="minus" data-iconpos="notext" data-theme="a">minus</a>
<a href="#" data-role="button" data-icon="check" data-iconpos="notext" data-theme="a">check</a>
<a href="#" data-role="button" data-icon="gear" data-iconpos="notext" data-theme="a">gear</a>
<a href="#" data-role="button" data-icon="refresh" data-iconpos="notext" data-theme="a">refresh</a>
<a href="#" data-role="button" data-icon="forward" data-iconpos="notext" data-theme="a">forward</a>
<a href="#" data-role="button" data-icon="back" data-iconpos="notext" data-theme="a">back</a>
<a href="#" data-role="button" data-icon="grid" data-iconpos="notext" data-theme="a">grid</a>
<a href="#" data-role="button" data-icon="star" data-iconpos="notext" data-theme="a">star</a>
<a href="#" data-role="button" data-icon="alert" data-iconpos="notext" data-theme="a">alert</a>
<a href="#" data-role="button" data-icon="info" data-iconpos="notext" data-theme="a">info</a>
<a href="#" data-role="button" data-icon="search" data-iconpos="notext" data-theme="a">search</a>
<a href="#" data-role="button" data-icon="home" data-iconpos="notext" data-theme="a">home</a>
<a href="#" data-role="button" data-icon="phone" data-iconpos="notext" data-theme="a">phone</a>
<a href="#" data-role="button" data-icon="mail" data-iconpos="notext" data-theme="a">mail</a>
```

```
</div>
```

**Selector / Switch**

Select Menu:

choice 1

```
<div data-role="fieldcontain">
  <label for="select-choice-1" class="select">Select Menu: </label>
  <select id="select-choice-1" data-theme="a">
    <option value="choice1">choice 1 </option>
    <option value="choice2">choice 2 </option>
    <option value="choice3">choice 3 </option>
    <option value="choice4">choice 4 </option>
  </select>
</div>
```

Switch :

[OnOff](#)

```
<div data-role="fieldcontain">
  <label for="switch">Switch : </label>
  <select id="switch" data-role="slider" data-theme="a">
    <option value="off">Off </option>
    <option value="on">On </option>
  </select>
</div>
```

[collapsible 1 click to expand contents](#)

collapsible 1 content

[collapsible 2 click to collapse contents](#)

collapsible 2 content

```
<div data-role="collapsible-set">
  <div data-role="collapsible" data-theme="a">
    <h3>collapsible 1 </h3>
    <p>collapsible 1 content </p>
  </div>
  <div data-role="collapsible" data-collapsed="false" data-theme="a">
    <h3>collapsible 2 </h3>
    <p>collapsible 2 content </p>
  </div>
</div>
```